


### **Electrical Specifications**

-	
<ul> <li>Frequency Range</li> <li>Gain</li> <li>Polarization</li> <li>Horizontal Beamwidth</li> <li>Vertical Beamwidth</li> <li>Downtilt</li> <li>VSWR</li> </ul>	2.4 – 2.5 GHz 5 dBi Linear, Vertical 360° (-3 dB) 30° (-3 dB) 0° 2 (Max.)
Impedance	50 Ω
<ul><li>Power Handling</li></ul>	10 W (cw)
0	( )

### **Environmental and Mechanical Specifications**

<ul> <li>Temperature</li> </ul>	-40 °C to +80 °C
Humidity	95% at 55 °C
<ul> <li>Radome Color</li> </ul>	Gray-white
<ul> <li>Radome Material</li> </ul>	Fiberglass, UV Resistant
<ul> <li>Weight</li> </ul>	110 g
<ul> <li>Dimensions</li> </ul>	322 x Ø21 mm
<ul> <li>Connector</li> </ul>	N-male

#### **Dimensions Diagram**







7.5

## **Antenna Patterns**

#### **H-plane Co-polarization**



# V-plane Co-polarization



# **Product Ordering Information**

• 2.4 GHz 5 dBi Omni Antenna (Part No.: SD.AN-2M05-00)

### **Contact Us**

• Email: sales@altaitechnologies.com

Although Altai has attempted to provide accurate information in these materials, Altai assumes no legal liability for the accuracy and completeness of the information. All specifications are subject to change without notice.